

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1.-7. (canceled)

8. (currently amended) An apparatus for positioning an external auxiliary processing device, which comprises one of a folder, a cross-cutting device, a sheet stacker, and a roll winding-up system, relative to a printing press, comprising:

a first positioning device mounted on the external auxiliary processing device;
and

a further positioning device arranged outside of the printing press and fixed to a floor relative to the printing press, said first positioning device being engagable with said further positioning device such that the external auxiliary processing device is reproducibly positionable at an operating position in relation to the printing press, wherein said first positioning device comprises a conical outer contour and said further positioning device has a complementary conical recess for engagably receiving said conical outer contour.

9. (canceled)

10. (previously presented) The apparatus of claim 8, wherein the auxiliary processing device has one of a mobile frame and lifting gear for providing mobility to the external auxiliary processing device.

11. (previously presented) The apparatus of claim 8, wherein said first positioning device further comprises a base piece for supporting the weight of the external auxiliary processing device when said first positioning device engages said further positioning device.

12. (currently amended) An The apparatus of claim 8, further comprising for positioning an external auxiliary processing device, which comprises one of a folder, a cross-cutting device, a sheet stacker, and a roll winding-up system, relative to a printing press, comprising:

a first positioning device mounted on the external auxiliary processing device;

a further positioning device arranged outside of the printing press and fixed to a floor relative to the printing press, said first positioning device being engagable with said further positioning device such that the external auxiliary processing device is reproducibly positionable at an operating position in relation to the printing press; and

a U-shaped receptacle arranged on the external auxiliary processing device and a cylindrical bolt arranged on the floor in relation to said further positioning device, wherein said cylindrical bolt is receivable in said U-shaped receptacle for aligning said first positioning device relative to said further positioning device.

13. (canceled)

14. (previously presented) The apparatus of claim 8, wherein two first positioning devices are arranged on the external auxiliary processing device corresponding to two further positioning devices mounted on the floor.